

DATA SHEET

EDGE-It® ECO TAPE

SUBSTRATE

CHARACTERISTIC	VALUE
CARRIER	100% POLYESTER, 275 G/M ²
TEAR STRENGTH	550/500 N
TENSILE STRENGTH	2800/2450 N/5CM
TEMPERATURE RESISTANCE	-20 TO 50°C (120°C SHORT TERM)
FIRE RATING	B1

ADHESIVE

CHARACTERISTIC	VALUE
ADHESIVE	ACRYLIC
PEEL ADHESION	PSTC-3 2.0KGS/25MM
SHEAR STRENGTH	PSTC-7 OVER 24 HOURS WITH 1KG LOADING ON 25MM X 25MM
SERVICE TEMPERATURE	-30 TO 120°C

PRODUCT FEATURES AND APPLICATIONS

100% PVC FREE

HIGH PERFORMANCE REINFORCEMENT FOR USE IN INDUSTRIAL APPLICATIONS

SUITABLE FOR USE ON PET, PP, BIODEGRADABLE AND VARIOUS FABRICS

LIGHTWEIGHT AND VERY STRONG

EXTERNAL LIFE 12 MTHS OR LONGER

THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE AND THE USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

DATE OF ISSUE : APRIL 2023