



DATA SHEET

H999 1.1MM DOUBLE COATED WHITE ACRYLIC FOAM

CHARACTERISTIC	VALUE
ADHESIVE	ACRYLIC
LINER	RED LOW DENSITY POLYETHYLENE FILM
CARRIER	ACRYLIC FOAM
ADHESIVE STRENGTH	55 N/25 MM
DYNAMIC SHEAR	7.5 KG/CM ²
TOTAL THICKNESS	1.1 MM
SERVICE TEMPERATURE	-40°C TO +90°C
RECOMMENDATIONS FOR USE	TEMPERATURE: BETWEEN +15°C AND +30°C SURFACE MUST BE CLEAN, DRY, DUST & GREASE FREE. INDICATED PERFORMANCE LEVEL ACHIEVED AFTER A BONDING PERIOD OF 24HRS AT +23°C
COLOUR	WHITE
SHELF LIFE AND STORAGE	2 YEARS MINIMUM SUBJECT TO STORAGE IN A CLEAN, DRY, VENTILATED AREA AT BETWEEN +10°C & +30°C

PRODUCT FEATURES AND APPLICATIONS

A PERMANENT BONDING ACRYLIC FOAM TAPE FOR INTERIOR AND EXTERIOR USE. REPLACES RIVETING, WELDING, LIQUID GLUES AND OTHER PERMANENT FASTENERS. SUITABLE FOR MAKING A SECURE BOND TO A VERY WIDE RANGE OF SUBSTRATES. IDEAL FOR BONDING SIGNS, PANELS, EMBLEMS, NAMEPLATES, METAL, PLASTICS, ELECTRONIC DISPLAYS AND WINDOW AND DOOR ESSEMBLY.

THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE AND THE USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

DATE OF ISSUE : JULY 2025